RF 44x24mm Roll Label

The RF 44x24mm label delivers dependable performance and merchandise protection using Radio Frequency (RF) technology. The printed copy on the face of the label is designed to visually inform potential thieves that items are protected by a security label and that carrying protected merchandise through the detection zone will alarm the pedestal system.

The label's small footprint minimizes impact on brand promotion and important product information, allowing application on virtually any package size.

Available for in-store hand application, this label can also be applied to merchandise at the point of manufacturing. This allows retailers to receive floor-ready merchandise with consistent label placement to help expedite receiving and selling floor fulfillment.

Retailer Values

- Provides visual deterrence while minimizing impact on brand promotion and important product information
- Protects merchandise by tagging at the point of manufacturing so merchandise arrives shelf-ready
- Permits open merchandising while still combatting theft

Product Codes

XL4424-DCP2KAL: Custom Print
XL4424-DPW2KAL: White

Technology

RF (8.2MHz +/- 5%)

Product Compatibility

Sensormatic RF detection and deactivation devices.

Environmental Constraints

Temperature
12°-25°C (54°-77°F)

Humidity
55% maximum

Shelf Life
Two years from date of manufacture when labels are stored between 12°-25°C (54°-77°F).

Mode of Application

Hand or Tabletop

Materials of Construction

Small Roll
70μm AL+15μm CPP+10μm AL

Hot Melt Adhesive
934E Henkel

Dimensions

Color .... Custom Print, White
Length .... 24mm ± 0.5mm
(0.94in ± 0.0197in)
Width .... 44mm ± 0.5mm
(1.73in ± 0.0197in)
Thickness .... 0.20mm ± 0.015mmm
(0.0078in ± 0.0006in)
Liner Width .... 48mm ± 1.0mm
(1.89in ± 0.0394in)
Liner to Liner Spacing .... 3mm ± 0.5mm
(0.12in ± 0.0197)

Note:

Warranty terms and conditions are as specified in the applicable Sales Agreement.

CE This product is in conformity with RoHS Directive 2011/65/EU, 2015/863/EU and REACH regulation as defined in EC No 1907/2006 and subsequent amendments.

Roll Specifications

	Small Roll		Small Roll
Product Code	XL4424-DCP2KAL XL4424-DPW2KAL	Product Code	XL4424-DCP2KAL XL4424-DPW2KAL
Diameter of Core	76mm (3in) core	External Carton Dimensions	44 x 23 x 16cm (17.32 x 9.06 x 6.30in)
Max Roll Diameter	150mm (5.91in)	External Cubic Ft. Per Case	0.60
Number Splices	6 maximum	Labels per Roll	2,000
Roll Weight	0.77kg (1.69lbs)	Rolls Per Case	10
Case Weight (gross)	8.45kg (18.64lbs)	Cases Per Pallet	80